



Standard & Optional Equipment / Features

Model 135 / 150 Fixed Gooseneck Beavertail



S=Standard O=Optional

MODEL 150	50 TON	100,000 lbs.		MODEL 150	50 TON	100,000 lbs.		
MODEL 135	35 TON	70,000 lbs.		MODEL 135	35 TON	70,000 lbs.		
MAIN FRAME - Fabricated 80,000 and 100,000 F - Four Beam Design - Capacity - 70,000 lb. Distributed / - Capacity - 100,000 lb. Distributed	50,000 lb. Concentrated		\$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$ \$	SUSPENSION - Multi-Leaf Springs 45,000 lb. Cap - Multi-Leaf Springs 67,200 lb. Cap - Neway Air Ride RLU228 22,500 l	acity H9700/60" Spread		s o	s O
KINGPIN SETTING - 18" Setting - 84" Swing Clearance	770,000 lb. Concentrates	7111 10	S S S	BRAKES - Automatic Slack Adjusters - Full Air with Spring Brakes - ABS, Rockwell 4S2M			s s	s s
CROSSMEMBERS - 4" Jr. I-Beam on 8" Centers			s s	OIL SEAL HUBS - Internal Mated Assembly			s	s
DECK AND FEATURES - 102" Width - Lower Deck Length 13527'3½", 29'3½", 32'3½"			s s s	TIRES / WHEELS - 235/75R 17.5 Double Coin - Hub Pilot / Steel Outboard Brake	Drum		s s	S
150-293½", 233½" - 90° Slope Drop - 37½" Deck Height (Loaded) - 1¾" Nominal, Apitong (Lower De			5 5 5 5 5 5 5 5	RIMS - 17.5x6.75 Tubeless - 17.5 Aluminum Wheels (8-Bolt Po	olished)		s o	s o
- 13" Loaded Ground Clearance UPPER DECK WINCH OPT - 12,000 lb. Worm Gear - 20,000 lb. Planetary - 20,000 lb. Worm Gear Winch - Cable Roller Guide for Winch — 1.	TIONS	o or Upper Dock	0 0 0 0 0 0	TIRES & RIMS - Spare Double Coin Tire and Hub - 235/75R 17.5 Michelin Tires in Lie - 255/70R 22.5 Michelin Tires in Lie - Hubometer - 255/70R 22.5 Double Coin Tires in	eu of Standard eu of Standard		00000	00000
TIE DOWNS / CHAIN GOTO - Double Key Hole Chain Slots Loc - "D" Ring Bolt-On at Winch (each) - Flush Mounted "D" Rings (each)	CHAS cated on 24" Centers	$\frac{1}{1}$	\$ \$ 0 0 0 0	HYDRAULIC POWER SOU Air Shift PTO and Wet Kit for Trac Installation of PTO and Wet Kit Hydraulic Quick Couplers I Male	tor - Not Installed	nc.	0	0 00
TOOL BOX - Twin Lockable Upper Deck Moun	ited with Lockable Door 7	'H x 34" W x 29" D	s s	HYDRAULIC HOOK UP - Hydraulic Quick Couplers 2,500 F	PSI - 15 GPM		0	o
DECK ACCESSORIES - Lower Deck Lockable Tool Box (Curb Side or Street Side) (42" W x 28"D x 9" H) - 96" Width Not Available SLOPE RAMP - 5" Aluminum Ramps (Portable) 8,000 lb. Capacity Each			0 0	AIR / ELECTRICAL CONNECTION - 7-Way Receptacle (Electrical)			s	s
			0 0	LIGHTS - Grote "SuperNova" LED 10-Year 7-Year Warranty - Center Mounted Side Turn Signal	*	e Seal" Wiring Harness	s s	s s
- Upper Deck Ramp (Air Operated) - Landoll Traction Ramps (Steel) BULKHEADS - 16" / 24" 2-Position Bulkhead / Front Extension (Solid)			0 0	FINISH / COLOR - Steel Grit Shot Blast to Bright Me - Epoxy Primer			SSS	SSS
- 48" High Mesh 102" or 96" Wide - Bolt-On Binder Storage Rack for - LED Work Light-Dual (Mounted o - Spare Tire Carrier 48" Bulkhead F - Spare Tire Carrier 48" Bulkhead F	48" Bulkheads on Bulkheads) Front Mounted Rear Mounted		0 0 0 0 0 0 0 0 0 0	- Acrylic Urethane White, Black, Ye RAMPS - 5' Self-Cleaning Adjustable Spring - Heavy Duty Crawler Ramp (Woo - Third Ramp—Self-Cleaning or Wo	g Assisted Flip-Over d Filled)		s 0 0	s 0 0
- Dual Spare Tire Carrier 48" Bulkhead, Front Mounted PARKING STANDS - Two Speed Landing Gear - Pin Drop (Lieu of Standard)			s s 0 0	BEAVERTAIL - 68" Self-Cleaning Beavertail - Apitong Wood Covered Beavertail - Traction Bars for Wood Covered Beavertail			s 0 0	\$ 0 0
AXLES - (2) 25,000 Dual Tire, Oil Bath Bea - (3) 25,000 Dual Tire, Oil Bath Bea			s s	WEIGHT - 135-40 12,000 lbs. +/- 3% - 150-48 14,500 lbs. +/- 3%			s	s

Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.

Proven Solutions for Your Hauling Needs! Remember: Quality is Always a Bargain!