

## Eastern Wrecker Sales, Inc.

LANDOLI



LANDOLLE

The multi-purpose ramps conveniently store on the upper deck.



The dual ramps are supplied as a standard feature. There is the flexibility of using one or two sets to achieve 5° load angle.



Ramps are designed to handle low front clearance of 5°, (the lowest load angle in the industry).



The mechanical wheel well lifter allows the bus to smoothly transition over the rear wheel wells.



Big jobs take special equipment: ramps, load angle, winch, wheel wells, remote control... It's a total package.



Adjustable wheel well pockets with five different positions minimize the clearance under the bus as well as lowers the overall height.

## **Proven Solutions for Your Hauling Needs!**

Eastern Wrecker Sales, Inc www.easternwrecker.com - 919-553-4038





## Standard & Optional Equipment / Features

## Model 353 Bus Hauler Trailer



s

s

S

S

SSSS

S

s s

s s

S

S=Standard O=Optional

MODEL 353 37.5 TON	75,000 lb.		MODEL 353	37.5 TON	75,000 lb.		
MAIN FRAME - Fabricated 80,000 and 100,000 PSI Yield Four Beam Frame - Capacity - 50,000 lbs. in 10'  KINGPIN SETTING		S S	TOOL BOX - Twin Upper Deck Lockable Tool Boxes - 6.75" x 27.75" x 31 - Twin Lower Deck Lockable Tool Boxes - 8.75" x 24" x 31" - Storage for Outrigger Foot Pads  PARKING STANDS - Jost Two Speed				
- 17.5" Setback, 75.5" Swing Clearance - 2" Fifth-Wheel Kingpin Hitch		S S					
CROSSMEMBERS - 4" Jr. I-Beam on 16" Centers		s	SUSPENSION / AXLES - Neway Air Ride RLU228 22,500 lb. Capacity - (3) 25,000 lb. Dual Tire, Oil Bath Bearings - Centralized Grease System				
WINCH - 12,000 lb. Worm Gear with Spring Tension and 85' of 1/2" Cable - 20,000 lb. Worm Gear with Spring Tension and 85' of 1/2" Cable - 30,000 lb. Planetary with Air Release and 85' of 1/2" Cable - Dual Slope Rollers (Routes Cable to 6" Off Lower Deck)		s					
		0 0 S	BRAKES - 12.25x7.5 Full Air with Spring Brakes (Two Axles) ABS 4S2M				
DECK AND FEATURES  - 102" Wide  - Steel Tread Plate  - 26" Loaded Deck Height (In Dropped Area and Wells)  - 5° Load Angle  - 11" Loaded Ground Clearance  - Mechanical "Well Lift" System  - Hydraulic Outrigger with Side Shift Hydraulic Capability  ACCESORIES  - (1) pair Aluminum Ramps Multi-Position (96")  - (1) pair Aluminum Ramps Approach or Slope (60")		s	- Automatic Slack Adjusters  TIRES / WHEELS - 215/75R 17.5 LRH Double Coin - 17.5x6.75 Tubeless Rims - Pressure Guard Tire Inflation System - Hub-Pilot / Steel Outboard Brake Drums				
		SSS					
						S	
		S S				HYDRAULIC HOOK UP - Hydraulic Quick Couplers / 2,500 PSI - 15 GPM HYDRAULIC REMOTE CONTROLS - Full Manual Controls and Full Function Control by Wireless Remote Control	
		88 88					
			TIE DOWNS / CHAIN GOTCHAS  - Double Keyhole Tie Downs on Approach Plate  - Double Keyhole Chain Slots with Square Stake  - Pockets on 32" Centers (Estimated)		LIGHTS / WIRING HARNESS - Grote "SuperNova" LED 10-Year Warranty - Grote "Ultra-Blue Seal" 7-Year Warranty		
Pictures and content may include optional equipment and/or standard features that may not be standard on all models. Specification and design subject to change without notice. Weights and measurements are best estimates and should not be treated as actual. There are other features and optional equipment available. If you have any questions, consult the factory.					- Steel Grit Shot Blast to Bright Metal - TGIC Polyester Powder Coat - White, Black, Yellow, Blue,		





SPECIFICATIONS SUBJECT TO CHANGE



Outrigger Lift System

**Proven Solutions for Your Hauling Needs!** 

Red, Green WEIGHT

-26,140 lbs. (53') +/- 3%

Remember: Quality is Always a Bargain!

Eastern Wrecker Sales, Inc www.easternwrecker.com - 919-553-4038