



KEY FEATURES

- **DECK:**
Built to be tough and reliable with aluminum construction. 17,000-lb structural capacity.
- **WINCH:**
Up to 10,000-lb capacity winch for maximum pulling power.
- **WHEEL LIFT:**
Low profile and versatile. Various grid options available. 3,500-lb or 5,000-lb lift capacities.

SPECIFICATIONS

CARRIER DECK	
Capacity	17,000-lb
Deck Width	102-in
Deck Length	22-ft, 24-ft, 28-ft, 30-ft
Material Type	Aluminum
WHEEL LIFT- 3,500-LB	
Lift Capacity	3,500-lb
Tow Capacity	10,000-lb
Maximum Extended Reach from Tail to Bed	65-in
WHEEL LIFT- 5,000-LB	
Lift Capacity	5,000-lb
Tow Capacity	12,000-lb
Maximum Extended Reach from Tail to Bed	67-in
WINCH	
Winch Capacity	Single 10,000-lb Dual 8,000-lb
10K Single Winch	22-ft & 24-ft Deck Only
8K Dual Winch	28-ft & 30-ft Deck Only
CHASSIS	
Minimum GVWR (w/o Wheel Lift)	25,500-lb
Minimum GVWR (w/ Wheel Lift)	33,000-lb
Cab to Axle (CA) Range	138-in - 150-in (22-ft Deck) 156-in - 168-in (24-ft Deck) 180-in - 192-in (26-ft Deck) 204-in - 214-in (28-ft Deck) 228-in - 238-in (30-ft Deck)



Visit jerrdan.com for more info on warranty.

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
DECK & SUBFRAME		
High Strength Extruded Aluminum Panels	•	
Patented Galvanized Steel Main Beams	•	
5-in Fixed Blade Rails (NGAF)	•	
102-in Deck Width	•	
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Rear Subframe Chain Boxes with Safety Chains	•	
Hi Vis Reflective Tape Rear of Sub Frame		•
Deck Approach Tip Rollers		•
Greaseable Pivot Joints (Cylinders and Pivot Pins)		•
Side Recovery System (SRS) (SRS-10K) Available with Combo Remote (16-in of Frame Clear Space Required)		•
Galvanized Subframe & Wheel Lift		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•
ACCESSORIES		
Air Supply Disconnect (End of Subframe Mounted at LH Taillights)		•
SS Quarter Fenders		•
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Strap and Chain Kit: • 2- 2-in x 96-in Strap w/RTJ Hook • 2- 2-in Ratchet w/12-in Chain • 2- 5/16-in x 10-ft Chain, RTJ Hooks One End and Grab Hook on the Other • 1- 5/16-in V-Chain w/RTJ Hooks Each End and Grab Hooks at Center	•	
8 Point Tie Down Kit		•
Trailer Glad Hands & 7 Way Connector with Mounting Bracket		•
Wheel Lift Grids (Manual L Arms or Autogrid)		•
Camlocks ILO of T-Handle Manual L Arms		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids) 2-in or 2.5-in Reese Available		•
Hydraulic Rear Dock Stabilizer (Various Trailer Towing Provisions Available) *Option Available when Wheel Lift is Deleted		•
WINCH & WIRE ROPE		
10,000-lb Worm Gear Winch w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope (Only Available on 22-ft & 24-ft)		•
Dual 8,000-lb Worm Gear Winches w/ 3/8-in x 56-ft EIPS Galvanized Wire Rope (Only Available on 28-ft & 30-ft)		•
Dual Side Manual Free Spool (10,000-lb Winch Only)		•
Air Controlled Winch Free Spool (10,000-lb Winch Only)		•
HEADBOARD		
Adjustable Headboard Height 45.5-in - 65.5-in Class 6 and Above Chassis		•
Deluxe Headboard Height 36.5-in, 45.5-in, 50.5-in, 57.5-in		•
Stationary Headboard Base Mount, Fits Standard Deck Mounted Headboards to Frame Mounted Stationary (12-in Clear Space Required)		•
Headboard Mounted Chain Racks		•
Headboard Mounted Propane Tank Holder		•
Headboard Mounted Side Grab Handles		•